

SPECIFICATION

Product Standard DIN EN ISO 10582

Properties	Standard	Unit / Requirements	Construction
Thickness	EN ISO 24346	mm	2,5
Wearlayer	EN ISO 24340	mm	0,55
Weight	EN ISO 23997	g/m ²	ca. 4310

PERFORMANCE

Classification	EN ISO 10874	Class	
Fire Classification	EN 13501-1	Class	B _{fl} -s1
Slip resistance	DIN 51130	Class	R10
Residual Indentation	EN ISO 24343-1	mm	≤ 0,1
Thermal Conductivity	EN 12664	(W/m*K)	0,091
Thermal Resistance	EN 12664	(m ² *K)/W	0,028
Electrostatic Behaviour	EN 1815 Method A	kV	0,1
Dimensional Stability	EN ISO 23999	%	≤ 0,25
Castor Chair	EN ISO 4918		Yes, Type W
Colour Fastness	ISO 105-B02	Grade	6
Sound Absorption	EN ISO 10140-3	dB	approx. 3
Chemical Resistance	EN ISO 26987		Yes
Floor Heating System		° C	Yes, max. 27
CE Marking	EN 14041		

SPECIFICATION

Product Standard DIN EN ISO 10582

Properties	Standard	Unit / Requirements	Construction
Thickness	EN ISO 24346	mm	2,5
Wearlayer	EN ISO 24340	mm	0,55
Weight	EN ISO 23997	g/m ²	ca. 4310

PERFORMANCE

Classification	EN ISO 10874	Class	
Fire Classification	EN 13501-1	Class	B _{f1} -s1
Slip resistance	DIN 51130	Class	R10
Residual Indentation	EN ISO 24343-1	mm	≤ 0,1
Thermal Conductivity	EN 12664	(W/m*K)	0,091
Thermal Resistance	EN 12664	(m ² *K)/W	0,028
Electrostatic Behaviour	EN 1815 Method A	kV	0,1
Dimensional Stability	EN ISO 23999	%	≤ 0,25
Castor Chair	EN ISO 4918		Yes, Type W
Colour Fastness	ISO 105-B02	Grade	6
Sound Absorption	EN ISO 10140-3	dB	approx. 3
Chemical Resistance	EN ISO 26987		Yes
Floor Heating System		° C	Yes, max. 27
CE Marking	EN 14041	CE	

SPECIFICATION

Product Standard DIN EN ISO 10582

Properties	Standard	Unit / Requirements	Construction
Thickness	EN ISO 24346	mm	2,5
Wearlayer	EN ISO 24340	mm	0,55
Weight	EN ISO 23997	g/m ²	ca. 4310

PERFORMANCE

Classification	EN ISO 10874	Class	
Fire Classification	EN 13501-1	Class	B _{f1} -s1
Slip resistance	DIN 51130	Class	R10
Residual Indentation	EN ISO 24343-1	mm	≤ 0,1
Thermal Conductivity	EN 12664	(W/m*K)	0,091
Thermal Resistance	EN 12664	(m ² *K)/W	0,028
Electrostatic Behaviour	EN 1815 Method A	kV	0,1
Dimensional Stability	EN ISO 23999	%	≤ 0,25
Castor Chair	EN ISO 4918		Yes, Type W
Colour Fastness	ISO 105-B02	Grade	6
Sound Absorption	EN ISO 10140-3	dB	approx. 3
Chemical Resistance	EN ISO 26987		Yes
Floor Heating System		° C	Yes, max. 27
CE Marking	EN 14041	CE	

OTIUM. AT HOME

CHEVRON

DRYBACK

2,5 / 0,55

PHTHALATE-FREE HETEROGENOUS
LUXURY VINYL TILE

SPECIFICATION

Product Standard DIN EN ISO 10582

Properties	Standard	Unit / Requirements	Construction
Thickness	EN ISO 24346	mm	2,5
Wearlayer	EN ISO 24340	mm	0,55
Weight	EN ISO 23997	g/m ²	ca. 4310

PERFORMANCE

Classification	EN ISO 10874	Class	
Fire Classification	EN 13501-1	Class	B _{f1} -s1
Slip resistance	DIN 51130	Class	R10
Residual Indentation	EN ISO 24343-1	mm	≤ 0,1
Thermal Conductivity	EN 12664	(W/m*K)	0,091
Thermal Resistance	EN 12664	(m ² *K)/W	0,028
Electrostatic Behaviour	EN 1815 Method A	kV	0,1
Dimensional Stability	EN ISO 23999	%	≤ 0,25
Castor Chair	EN ISO 4918		Yes, Type W
Colour Fastness	ISO 105-B02	Grade	6
Sound Absorption	EN ISO 10140-3	dB	approx. 3
Chemical Resistance	EN ISO 26987		Yes
Floor Heating System		° C	Yes, max. 27
CE Marking	EN 14041		

